


- Barreled ends for greater holding power.
- Smooth, rounded edges ensure that Lockit Clips won't cut into cable's insulation—or the installer's hand.
- Releasable and reusable loops for easy wire bundling.
- Locking ends twist into place with fingertip pressure.
- Part Description Key: LL XXX, where XXX = Maximum Bundle Diameter (inches).

## HEYClip™ Lockit™ Loops Standard Loops

MAXIMUM BUNDLE DIAMETER		PART NO. Natural	DESCRIPTION	OVERALL HEIGHT C	
in.	mm.			in.	mm.
<b>LL Series</b>					
.25	6,4	<b>3793</b>	LL 250	.84	21,2
.38	9,5	<b>3795</b>	LL 375	1.02	25,9
.50	12,7	<b>3797</b>	LL 500	1.20	30,4
.75	19,1	<b>3799</b>	LL 750	1.45	36,8

Standard color natural.



- Part Description Key (part numbers **4155** thru **4172** only): PMLL XX-YY, where XX = Maximum Bundle Diameter (inches) and YY = Height Above Panel (inches).



## Standoff Loops - Arrowhead Mount

MAXIMUM BUNDLE DIAMETER		PART NO. Natural	DESCRIPTION	SPACER HEIGHT A		OVERALL LENGTH ABOVE PANEL C		MOUNTING HOLE	
in.	mm.			in.	mm.	in.	mm.	in.	mm.
<b>PMLL Series</b> For Panels from .03" (0,8 mm) - .08" (2,0 mm) thick									
.28	7,0	<b>4155</b>	PMLL 28-19	.19	4,8	.94	23,9	.236	6,0
		<b>4156</b>	PMLL 28-50	.50	12,7	1.25	31,8		
		<b>4157</b>	PMLL 28-75	.75	19,1	1.50	38,2		
		<b>4158</b>	PMLL 28-100	1.00	25,4	1.75	44,5		
.39	10,0	<b>4160</b>	PMLL 39-19	.19	4,8	1.10	27,9		
		<b>4161</b>	PMLL 39-50	.50	12,7	1.41	35,8		
		<b>4162</b>	PMLL 39-75	.75	19,1	1.66	42,2		
		<b>4163</b>	PMLL 39-100	1.00	25,4	1.91	48,5		
.50	12,5	<b>4165</b>	PMLL 50-19	.19	4,8	1.28	32,5		
		<b>4166</b>	PMLL 50-50	.50	12,7	1.59	40,4		
		<b>4167</b>	PMLL 50-75	.75	19,1	1.84	46,8		
		<b>4168</b>	PMLL 50-100	1.00	25,4	2.09	53,1		
.59	15,0	<b>4170</b>	PMLL 59-19	.19	4,8	1.47	37,2		
		<b>4171</b>	PMLL 59-50	.50	12,7	1.78	45,2		
		<b>4172</b>	PMLL 59-75	.75	19,1	2.03	51,6		
		<b>4173</b>	PMLL 59-100	1.00	25,4	2.28	57,9		
For Panels up to .09" (2,4 mm) thick									
.25	6,4	<b>3778</b>	PMLL 250	.14	3,6	.93	23,6	.185	4,7
.38	9,5	<b>3779</b>	PMLL 375						
.50	12,7	<b>3780</b>	PMLL 500						
.75	19,1	<b>3782</b>	PMLL 750						
For Panels up to .06" (1,5 mm) thick									
1.00	25,4	<b>3796</b>	PMLL 1000	.14	3,6	2.22	56,4	.250	6,4

Standard color natural.

Material	Nylon 6/6
Flammability Rating	94V-2
Temperature Range	32°F (0°C) to 185°F (85°C)

Quick  
Specs