




HEYClip™ Tension Wire Clips - Vinyl U Style

Adhesive-Back Mount



MAXIMUM BUNDLE DIAMETER A		PART NO. Gray	DESCRIPTION	OVERALL HEIGHT D*		FOOTPRINT** B x C	
in.	mm.			in.	mm.	in.	mm.
WCUA Series							
.13	3,2	3335	WCUA 125	.29	7,4		
.25	6,4	3336	WCUA 250	.47	11,9	.75 x .75	19,1 x 19,1
.38	9,5	3337	WCUA 375	.59	15,1		
.50	12,7	3338	WCUA 500	.61	15,5		
.56	14,3	3339	WCUA 562	.64	16,3	1.00 x 1.00	25,4 x 25,4
.75	19,1	3341	WCUA 750	.90	22,9		
WCDA Series							
.25	6,4	3821	WCDA 250	.40	10,2	.50 x .50	12,7 x 12,7
.50	12,7	3822	WCDA 500	.73	18,5	.75 x .75	19,1 x 19,1
.75	19,1	3823	WCDA 750	1.02	25,9	1.13 x 1.00	28,7 x 25,4
1.00	25,4	3824	WCDA 1000	1.30	33,0	1.50 x 1.25	38,1 x 31,8



NEW PRODUCT!

Standard color gray.



* At maximum wire capacity.

** Custom lengths available by special order, consult Heyco.

- Manufactured from a general purpose PVC with an excellent NFPA fire and flame resistance rating.
- The compact design combined with a strong acrylic based adhesive provides a low cost means of routing cable or tubing.



WCUA



WCDA

Material: PVC
 Flammability Rating: 94V-0
 Temperature Range: -20°F (-29°C) to 150°F (66°C)

Quick
Specs