

"Stay Connected with Heyco" Strain Relief Bushings



Heyco® Original Strain Relief Bushings


Right Angle for Round Cables

- Provides the same protection for your power supply cable as the straight-thru type AND...
- **Exits the cable flush against the panel**, saving space and directing the cable parallel to the panel.
- Overcomes space limitations and acts as a back or bottom bumper.
- See page 4-38 for corresponding **Mounting Hole Plugs** which can be used to fill blank/unused Mounting Holes and thus allow for a single panel design for multiple applications.
- Consult Heyco for other wire types and sizes.
- See pages 4-27 & 4-28 for SR assembly tools.


UL Type	WILL FIT THESE CABLES		PANEL DIMENSIONS						PART NO. Black	DESC	PART DIMENSIONS				Mounting Hole Plug PART NO.									
	AWG/ Conductors	Approximate Size	A Mounting Hole Dia.		B To Prevent Rotation		Finished Fit Panel Thickness*				C HEAD LENGTH		D BODY LENGTH											
		in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.	in. mm.											
SV & SVT	18/2	.250 6,4	.500 12,7	.450	11,4	.100	2,5	1374	SR 15-1	.390	9,9	.687	17,5	2491										
	18/3	.265 6,7	.500-.515 12,7-13,1																					
HPD	18/2	.270 6,9	.500 12,7	.450	11,4	.100	2,5	1374	SR 15-1	.390	9,9	.687	17,5	2491										
	16/2	.290 7,4	.500-.515 12,7-13,1																					
SJ, SJO & SJT	18/2	.300 7,6	.625 15,9	.550	14,0	.062	1,6	1323	SR 10N-2	.562	14,3	.968	24,6	2497										
	16/2	.325 8,3																						
	18/3	.330 8,4																						
SJ	16/3	.330 8,4	.625 15,9	.550	14,0	.125	3,2	1320	SR 10-2	.562	14,3	.968	24,6	2497										
Same as SR 10N-2 above except																								
SJ, SJO & SJT	16/2	.325 8,3													.625 15,9	.550	14,0	.125	3,2	1327	SR 11-2	.562	14,3	.968
	18/3	.330 8,4																						
	16/3	.335 9,0																						
Same as SR 11-2 above except						.200	5,1	1330	SR 11K-2	.562	14,3	.968	24,6	consult Heyco										
SJT	18/4	.360 9,1	.750 19,0	.660	16,8	.125	3,2	1397	SR 17-2	.640	16,3	1.093	27,7	2503										
SJT & SJTO	14/3	.370 9,4																						
SJ & ST	18/2	.390 9,9	.750-.781 19,0-19,8	.660	16,8	.125	3,2	1397	SR 17-2	.640	16,3	1.093	27,7	2503										
	18/3	.405 10,3																						
	16/2	.405 10,3																						

Standard color black. Consult Heyco for white and other colors.

*Maximum Panel Thickness. Part has additional clearance. Consult Heyco for your Custom Finished Fit Panel Thickness.



MOUNTING HOLES



Material	Nylon 6/6
Certifications	UL Recognized under the Component Program of Underwriters' Laboratories File E15331 SP Certified by the Canadian Standards Association File 8919
Flammability Rating	94V-2
Temperature Range	-04°F (-18°C) to 221°F (105°C)