



Heyco® PG Threaded Plugs

For PG Thread Specifications, see page 3-49

THREAD	PART NO.		DESCRIPTION	PART DIMENSIONS			
	Gray	Black		A Head Diameter		B Overall Height	
Type/Size				in.	mm.	in.	mm.
PG 7	3405	3405B	TP PG 7	.59	15,0	.32	8,0
PG 9	3407	3407B	TP PG 9	.75	19,0	.37	9,5
PG 11	3402	3402B	TP PG 11	.87	22,0		
PG 13	3412	3412B	TP PG 13	.98	25,0	.39	10,0
PG 16	3414	3414B	TP PG 16	1.06	27,0		
PG 21	3416	3416B	TP PG 21	1.30	33,0	.47	12,0
PG 29	3418	3418B	TP PG 29	1.73	44,0		
PG 36	3415	3415B	TP PG 36	2.17	55,0	.55	14,0
PG 48	3417	3417B	TP PG 48	2.72	69,0	.63	16,0


Standard colors gray and black.

- Protection Class IP 50.
- PG plugs are molded of shock resistant polystyrene and metric plugs are molded of Nylon 6.
- Consult Heyco for other colors.
- For PG Thread Specifications, see page 3-49.

Heyco® Metric Threaded Plugs

THREAD	PART NO.		DESCRIPTION	PART DIMENSIONS			
	Gray	Black		A Head Diameter		B Overall Height	
Type/Size				in.	mm.	in.	mm.
M12 x 1,5	3403	3403B	TP M12	.59	15,0		
M16 x 1,5	3404	3404B	TP M16	.79	20,0	.41	10,5
M20 x 1,5	3406	3406B	TP M20	.95	24,0		
M25 x 1,5	3408	3408B	TP M25	1.18	30,0	.51	13,0
M32 x 1,5	3409	3409B	TP M32	1.48	37,0	.53	13,5
M40 x 1,5	3410	3410B	TP M40	1.81	46,0	.55	14,0
M50 x 1,5	3411	3411B	TP M50	2.20	56,0	.63	16,0
M63 x 1,5	3413	3413B	TP M63	2.76	70,0	.71	18,0

Standard colors gray and black.



Materials	PG Metric	Shock Resistant Polystyrene Nylon 6
Flammability Rating		94V-2
Temperature Range		-4°F (-20°C) to 176°F (80°C)
IP Rating		IP 50

*Quick
Specs*